



**FLEX STP 40** is a high performance flexible LED fixture distinguished by its extremely tight LED pitch and ability to blend in shallow channels, making it perfect for direct view applications.

## ELECTRICAL

<b>Input Voltage</b>	24VDC
<b>Dimming Options</b>	<ul style="list-style-type: none"> <li>• PURE DC™</li> <li>• MLV</li> <li>• 0-10V</li> <li>• DMX</li> <li>• Lutron (2-WIRE, 3-WIRE, EcoSystem)</li> </ul>
<b>Power Consumption</b>	4.0 Watts per foot
<b>Wire Size</b>	20AWG, 2 wire
<b>Regulatory</b>	<p><b>ETL</b> - Conforms to UL Std. 2108; Certified to CSA Std. C22.2 No. 9.0</p> <p><b>Title 24</b> - Selected models are JA8 2016 compliant when used with 0-10V, DMX, or Lutron Premier dimming.</p>

## PHYSICAL

<b>Field Cuttable</b>	Every 0.90" (22.86mm)
<b>Operating Temperature</b>	-20° C (-40°F) to +50°C (+122°F)
<b>Environment</b>	IP20 - Dry Location
<b>Maximum Run Length</b>	24.00'
<b>Dimensions (WxH)</b>	0.39" (11.94mm) x 0.07" (1.78mm)

## ACCESSORIES

<b>Channels</b>	Optic Arts® Channel (pg. 3-7)
<b>Mounting Clips</b>	FLEXMNT.SIL.EXT12 (pg. 8)
<b>Connectors</b>	LC-I2P-M, LC-I2P-F (pg. 8)
<b>Strain Relief</b>	FLEX.ZIP (pg. 8)
<b>FLEXConfig-1 Accessories</b>	FLEXSTP.PFC.02.08, FLEXSTP.BSC.02.08, LO-18G-2C-W-72, LP-18G-2C-W-72, LO-18G-2C-W-SP, LP-18G-2C-W-SP (pg. 9)

## LUMEN OUTPUT

<b>1800K</b>	240.00 lm/ft 60.00 lm/Watt
<b>2350K</b>	313.00 lm/ft 79.00 lm/Watt
<b>2750K JA8 2016<sup>1</sup></b>	338.00 lm/ft 83.00 lm/Watt
<b>2930K JA8 2016<sup>1</sup></b>	350.00 lm/ft 87.00 lm/Watt
<b>3550K JA8 2016<sup>1</sup></b>	353.00 lm/ft 88.00 lm/Watt

Note: Stated lumen values have a tolerance of +/- 10%.

1: JA8 2016 when used with 0-10V, DMX, or Lutron Premier dimming.

## PERFORMANCE

<b>CRI</b>	<b>2350-3550K</b> = 95+, <b>1800K</b> = 90+
<b>TM-30</b>	See pages 17-21
<b>Lumen Maintenance</b>	When used in Optic Arts® CHS-S-1208 or larger channel: 50,000 Hours L70
<b>Binning Tolerance</b>	+/- 100K
<b>Warranty</b>	5 years

## PART NUMBER BUILDER

SERIES	+	IP RATING	+	COLOR	+	VOLTAGE	+	WATTAGE	+	CONFIGURATION	+	LENGTH
FLEXSTP		20 = IP20 - Dry Location		18 = 1800K 23 = 2350K 27 = 2750K <sup>1</sup> 29 = 2930K <sup>1</sup> 35 = 3550K <sup>1</sup>		24 = 24 VDC		40 = 4.0W		FLC1 = FLEX Config 1 FLC2 = FLEX Config 2 FLC3 = FLEX Config 3		XX = Custom Length



1: JA8 2016 when used with 0-10V, DMX, or Lutron Premier dimming.

## DIMENSIONS

Optic Arts® cuts all FLEX STP and Channel products to length per customer specifications. Each length of FLEX STP is fitted with a 6' wire lead (custom lengths available upon request) and packaged on a reel in an anti-static bag. Bags are labeled with fixture type, length and location (if applicable). Each piece of channel is labeled with fixture type, length and location (if applicable), and is bundled by fixture type.

- Due to the nature of the FLEX STP product, specific lengths may not fall exactly on a cutting point. In this case, Optic Arts® will always cut to the smaller dimension unless otherwise specified.
- Unless otherwise specified, channel is cut 15mm longer than FLEX STP.
- Some on-site assembly required. See installation guides for details.


### INDOOR FLEX STP 40



#### INDOOR DIMENSIONS

Width	0.39" (10.05mm)
Height	0.07" (1.78mm)
Cutttable Segment Length	0.90" (22.86mm)
Pitch Length	0.1285" (3.26mm)
Max Run Length	24.00' (7315.20mm)

### INDOOR FLEX STP 40




## MOUNTING OPTIONS - COMPATIBLE CHANNELS


[Click to access CHANNEL ACCESSORIES CATALOGUE >](#)

### KEY

#### DIFFUSION LEVEL:



#### CONFIGURATION:



### CHS-R-1208

• Click on channel titles below to access complete channel cut sheets.


## SMALL CHANNELS

### SMALL CHANNEL PART NUMBER BREAKDOWN:

CHANNEL	CHANNEL SIZE	CHANNEL TYPE	FINISH	LENS TYPE	LENS DIFFUSION	MOUNTING
CH-SM = Channel Small	LS = Lite Short LT = Lite Tall	SF = Surface RE = Recessed	SS = Satin Silver MB = Matte Black Anodized <sup>1</sup> BZ = Deep Bronze Anodized <sup>1</sup> WH = White Powder Coat <sup>1</sup> GY = Gray Powder Coat <sup>1</sup>	FL = Flat GZ = Grazer	CC = Clear <sup>4</sup> CF = Frosted <sup>4</sup> CM = Milky <sup>4</sup> <i>*Leave Blank for Grazer.</i>	NA = Direct Surface MC = Mounting Clip <sup>3</sup> RC = Rotating Clip <sup>3</sup>
			BL = Blue Powder Coat <sup>1</sup> RD = Red Powder Coat <sup>1</sup> YL = Yellow Powder Coat <sup>1</sup> CH = Chrome <sup>1</sup> CR = Custom RAL Powder Coat <sup>1</sup>		<i>4: Only compatible with Grazer Lens Type.</i>	<i>3: Not compatible with recessed options</i>
			<i>1: Special order finishes may increase order lead time and incur an added cost.</i>			

### CH-SM-LS-RE

(Previously Known As CHS-R-1208)



A: 0.68" (17.25mm)  
B: 0.98" (25.00mm)  
C: 0.34" (8.60mm)



#### MATERIAL

Anodized Aluminum.

#### DESCRIPTION

Small - Short - Recessed - Channel.

#### LENGTH

7 Ft.

#### LENS TYPES


Clear CH-SM-LN-FL-CC  
Frosted CH-SM-LN-FL-CF  
Milky CH-SM-LN-FL-CM

#### ACCESSORIES

Endcap CH-SM-LS-RE-FL-EC  
Endcap w/hole CH-SM-LS-RE-FL-ECH

### CH-SM-LS-SF

(Previously Known As CHS-S-1208)



A: 0.68" (17.25mm)      D: 0.40" (12.70mm)  
B: 0.50" (12.59mm)      E: 0.78" (19.90mm)  
C: 0.34" (8.60mm)



#### MATERIAL

Anodized Aluminum

#### DESCRIPTION

Small - Short - Surface - Channel.

#### LENGTH

7 Ft.

#### LENS TYPES


Clear CH-SM-LN-FL-CC  
Frosted CH-SM-LN-FL-CF  
Milky CH-SM-LN-FL-CM

#### ACCESSORIES

Endcap CH-SM-LS-SF-FL-EC  
Endcap w/hole CH-SM-LS-SF-FL-ECH  
Mounting Clip CH-SM-LE-MC  
Rotating Mounting Clip CH-SM-LE-MC-R

### CH-SM-LT-RE

(Previously Known As CHS-R-1715)



A: 0.68" (17.25mm)  
B: 0.48" (12.30mm)  
C: 0.59" (15.05mm)  
D: 0.98" (25.00mm)



#### MATERIAL

Anodized Aluminum

#### DESCRIPTION

Small - Tall - Recessed - Channel.

#### LENGTH

7 Ft.

#### LENS TYPES


Clear CH-SM-LN-FL-CC  
Frosted CH-SM-LN-FL-CF  
Milky CH-SM-LN-FL-CM

#### ACCESSORIES

Endcap CH-SM-LT-RE-FL-EC  
Endcap w/hole CH-SM-LT-RE-FL-ECH

### CH-SM-LT-SF

(Previously Known As CHS-S-1715)



A: 0.68" (17.25mm)      D: 0.66" (16.76mm)  
B: 0.48" (12.30mm)      E: 0.78" (19.90mm)  
C: 0.59" (15.05mm)



#### MATERIAL

Anodized Aluminum

#### DESCRIPTION

Small - Tall - Surface - Channel.

#### LENGTH

7 Ft.

#### LENS TYPES

Clear CH-SM-LN-FL-CC  
Frosted CH-SM-LN-FL-CF  
Milky CH-SM-LN-FL-CM

#### ACCESSORIES

Endcap CH-SM-LT-SF-FL-EC  
Endcap w/hole CH-SM-LT-SF-FL-ECH  
Mounting Clip CH-SM-LE-MC  
Rotating Mounting Clip CH-SM-LE-MC-R

## MOUNTING OPTIONS - COMPATIBLE CHANNELS

- Not Blended  
 Blended w/Milky Lens  
 **1** Configuration 1  
 **1a** Configuration 1 with Auxiliary Housing Accessory  
 **2** Configuration 2  
 **3** Configuration 3

## MEDIUM CHANNELS

### MEDIUM CHANNEL PART NUMBER BREAKDOWN:

CHANNEL	CHANNEL SIZE	CHANNEL TYPE	FINISH	LENS TYPE	LENS DIFFUSION	MOUNTING
CH-MD = Channel Medium	LS = Lite TL = Tall <sup>6</sup>	SF = Surface RE = Recessed <sup>4</sup>	SS = Satin Silver MB = Matte Black Anodized <sup>9</sup> BZ = Deep Bronze Anodized <sup>9</sup> WH = White Powder Coat <sup>9</sup> GY = Gray Powder Coat <sup>9</sup>	FL = Flat	CC = Clear CF = Frosted CM = Milky	NA = Direct Surface MC = Mounting Clip <sup>7</sup> RC = Rotating Clip <sup>7</sup> PD = Pendant <sup>7, 8</sup>
			BL = Blue Powder Coat <sup>9</sup> RD = Red Powder Coat <sup>9</sup> CH = Chrome <sup>9</sup> CR = Custom RAL Powder Coat <sup>9</sup>			

4: Not available for tall channel.

5: Only available in surface channel type.

6: Not available with recessed channel type or Tall channel size.


7: Not compatible with recessed options.

8: Not available with Lite option.

9: Special order finishes may increase order lead time and incur an added cost.

### CH-MD-LS-SF

(Previously Known As CHW-S-2010)



Mounting Clip

- A:** 0.93" (23.50mm)    **D:** 0.48" (12.19mm)  
**B:** 0.78" (20.00mm)    **E:** 1.02" (25.80mm)  
**C:** 0.39" (10.00mm)



**1**

**2**

**3**

#### MATERIAL

Anodized Aluminum

#### DESCRIPTION

Medium - Lite - Surface - Channel.

#### LENGTH

7 Ft.

#### LENS TYPES


Clear	CH-MD-LN-FL-CC
Frosted	CH-MD-LN-FL-CF
Milky	CH-MD-LN-FL-CM

#### ACCESSORIES

Endcap	CH-MD-LS-SF-FL-EC
Endcap w/hole	CH-MD-LS-SF-FL-ECH
Mounting Clip	CH-MD-LE-MC
Rotating Mounting Clip	CH-MD-LE-MC-R

### CH-MD-LS-RE

(Previously Known As CHW-R-2010)



- A:** 0.93" (23.50mm)  
**B:** 0.78" (20.00mm)  
**C:** 0.39" (10.00mm)  
**D:** 1.19" (30.24mm)



**1**

**2**

#### MATERIAL

Anodized Aluminum

#### DESCRIPTION

Medium - Lite - Recessed - Channel.

#### LENGTH

7 Ft.


#### LENS TYPES

Clear	CH-MD-LN-FL-CC
Frosted	CH-MD-LN-FL-CF
Milky	CH-MD-LN-FL-CM

#### ACCESSORIES

Endcap	CH-MD-LS-RE-FL-EC
Endcap w/hole	CH-MD-LS-RE-FL-ECH
Mounting Clip	CH-MD-LE-MC
Rotating Mounting Clip	CH-MD-LE-MC-R

### CH-MD-TL-SF



- A:** 0.90" (23.11mm)  
**B:** 0.75" (19.05mm)  
**C:** 1.02" (26.16mm)



**1**

**2**

**3**

#### MATERIAL

Anodized Aluminum

#### DESCRIPTION

Medium - Tall - Surface - Channel.

#### LENGTH

7 Ft.

#### LENS TYPES

Clear	CH-MD-LN-FL-CC
Frosted	CH-MD-LN-FL-CF
Milky	CH-MD-LN-FL-CM

#### ACCESSORIES

Endcap	CH-MD-TL-SF-FL-EC
Endcap w/hole	CH-MD-TL-SF-FL-ECH
Mounting Clip	CH-MC
Rotating Mounting Clip	CH-MC-R-AY
Pendant	CH-PD-KIT

## MOUNTING OPTIONS - COMPATIBLE CHANNELS


- Not Blended
 Blended w/Milky Lens
 **1** Configuration 1
 **1a** Configuration 1 with Auxiliary Housing Accessory
 **2** Configuration 2
 **3** Configuration 3

## LARGE CHANNELS

### CHANNEL PART NUMBER BREAKDOWN:

CHS	+	R	+	1208
SERIES		APPLICATION		DIMENSIONS
CHS = Slim Channel CHW = Wide Channel		S = Surface Mount R = Recessed Mount C = Corner Mount H = Hanging Mount		XXXX = W x H (mm)

### CHW-S-3535



- A:** 1.39" (35.25mm)  
**B:** 0.96" (24.50mm)  
**C:** 1.39" (35.25mm)  
**D:** 1.54" (39.00mm)

\*Must specify for hanging or surface mount application.



#### MATERIAL

Anodized Aluminum



#### DESCRIPTION

Wide and deep surface mounted or hanging channel. Eliminates visible LED nodes for most FLEXDC products when used with a milky lens.



#### LENGTH

2 meter




#### LENS TYPES

Frosted Milky CHW-35mm-CF  
Milky CHW-35mm-CM

#### ACCESSORIES

**Endcap** CHW-S-3535-EC  
**Endcap w/hole** CHW-S-3535-ECH  
**Mounting Clip** CHW-S-3535-MC  
**Hanging Hardware** CHW-SH-3535-MW  
**Bracket Straight** CHW-S-XX35-BS  
**Bracket 90° Flat** CHW-S-XX35-B90F  
**Bracket 90° Raised** CHW-S-XX35-B90R  
**End Cap for FLEX AC** CHW-S-3535-ECAC  
**Mounting Clip for FLEX AC** CHW-S-3535-MCAC  
**VHB Tape** VHBTAPE.AC

### CHW-R-4435



- A:** 1.39" (35.25mm)  
**B:** 0.96" (24.50mm)  
**C:** 1.39" (35.25mm)  
**D:** 2.00" (51.04mm)



#### MATERIAL

Anodized Aluminum



#### DESCRIPTION

Wide and deep recessed channel. Eliminates visible LED nodes for most FLEXDC products when used with a milky lens. Can be securely and conveniently mounted with CHW-R-4435-SC spring clip.



#### LENGTH

2 meter



#### LENS TYPES

Frosted Milky CHW-35mm-CF  
Milky CHW-35mm-CM


#### ACCESSORIES

**Endcap** CHW-R-4435-EC  
**Endcap w/hole** CHW-R-4435-ECH  
**Mounting Clip** CHW-R-4435-SC  
**Bracket Straight** CHW-S-XX35-BS  
**Bracket 90° Flat** CHW-S-XX35-B90F  
**Bracket 90° Raised** CHW-S-XX35-B90R  
**End Cap for FLEX AC** CHW-R-4435-ECAC  
**Mounting Clip for FLEX AC** CHW-R-4435-MCAC  
**VHB Tape** VHBTAPE.AC

## CORNER CHANNELS

### CHS-C-1919

Fits IP40 FLEX STP only



- A:** 0.73" (18.50mm)    **D:** 0.82" (20.82mm)  
**B:** 0.48" (12.20mm)    **E:** 0.82" (20.82mm)  
**C:** 0.73" (18.50mm)



#### MATERIAL

Anodized Aluminum



#### DESCRIPTION

Slim corner mount channel.



#### LENGTH

2 meter




#### LENS TYPES

Clear CHS-12mm-CC  
Frosted CHS-12mm-CF  
Milky CHS-12mm-CM

#### ACCESSORIES

**Endcap** CHS-C-1919-EC  
**Endcap w/hole** CHS-C-1919-ECH  
**Mounting Clip** CHS-C-1919-MC

### CHS-C-1616



- A:** 0.63" (16.00mm)    **D:** 0.70" (17.78mm)  
**B:** 0.39" (10.00mm)    **E:** 0.70" (17.78mm)  
**C:** 0.63" (16.00mm)



#### MATERIAL

Anodized Aluminum



#### DESCRIPTION

Slim corner mount channel with rounded lens.



#### LENGTH

2 meter



#### LENS TYPES

Frosted Milky CHS-C-1616-CF  
Milky CHS-C-1616-CM

#### ACCESSORIES


**Endcap** CHS-C-1616-EC  
**Endcap w/hole** CHS-C-1616-ECH  
**Mounting Clip** CHS-C-1616-MC

## MOUNTING OPTIONS - COMPATIBLE CHANNELS

- Not Blended 
 Blended w/Milky Lens 
 **1** Configuration 1 
 **1a** Configuration 1 with Auxiliary Housing Accessory 
 **2** Configuration 2 
 **3** Configuration 3

## CORNER CHANNELS

### CHW-C-3030



**A:** 1.18" (30.00mm)    **D:** 1.29" (32.77mm)  
**B:** 0.78" (20.20mm)    **E:** 1.29" (32.77mm)  
**C:** 1.18" (30.00mm)



**MATERIAL**  
Anodized Aluminum



**DESCRIPTION**  
45 degree channel with rounded lens.



**LENGTH**  
2 meter




**LENS TYPES**  
 Clear CHW-C-3030-CC  
 Frosted CHW-C-3030-CF  
 Milky CHW-C-3030-CM



**ACCESSORIES**  
 Endcap CHW-C-3030-EC  
 Endcap w/hole CHW-C-3030-ECH  
 Mounting Clip CHW-C-3030-MC

### CHW-C-3030S



**A:** 1.18" (30.00mm)    **D:** 1.29" (32.77mm)  
**B:** 0.78" (20.20mm)    **E:** 1.29" (32.77mm)  
**C:** 1.18" (30.00mm)



**MATERIAL**  
Anodized Aluminum



**DESCRIPTION**  
45 degree channel with square lens.



**LENGTH**  
2 meter




**LENS TYPES**  
 Clear CHW-C-3030S-CC  
 Frosted CHW-C-3030S-CF  
 Milky CHW-C-3030S-CM



**ACCESSORIES**  
 Endcap CHW-C-3030S-EC  
 Endcap w/hole CHW-C-3030S-ECH  
 Mounting Clip CHW-C-3030S-MC

## SPECIALTY CHANNELS

### CHS-S-1922R



**A:** 0.77" (19.50mm)  
**B:** 0.65" (16.50mm)  
**C:** 0.86" (21.80mm)



**MATERIAL**  
Anodized Aluminum



**DESCRIPTION**  
Slim surface mounted channel with rounded wrap around lens. Mounting clip is fully concealed within fixture base.



**LENGTH**  
2 meter




**LENS TYPES**  
Milky CHW-S-1922R-CM



**ACCESSORIES**  
 Endcap CHS-S-1922R-EC  
 Endcap w/hole CHS-S-1922R-ECH  
 Mounting Clip CHS-S-1922R-MC

### CHW-S-2623



**A:** 1.03" (26.20mm)  
**B:** 0.80" (20.35mm)  
**C:** 0.89" (22.76mm)



**MATERIAL**  
Anodized Aluminum



**DESCRIPTION**  
Surface mounted channel with wrap around lens.



**LENGTH**  
2 meter




**LENS TYPES**  
Milky CHW-S-2623-CM



**ACCESSORIES**  
 Endcap CHW-S-2623-EC  
 Endcap w/hole CHW-S-2623-ECH

### CHS-S-1922S



**A:** 0.77" (19.50mm)  
**B:** 0.65" (16.50mm)  
**C:** 0.86" (21.80mm)



**MATERIAL**  
Anodized Aluminum



**DESCRIPTION**  
Slim surface mounted channel with square wrap around lens. Mounting clip is fully concealed within fixture base.



**LENGTH**  
2 meter




**LENS TYPES**  
Milky CHW-S-1922S-CM



**ACCESSORIES**  
 Endcap CHS-S-1922S-EC  
 Endcap w/hole CHS-S-1922S-ECH  
 Mounting Clip CHS-S-1922S-MC

### CHW-S/H-2027



**A:** 0.79" (20.30mm)  
**B:** 0.66" (16.70mm)  
**C:** 1.06" (27.00mm)  
**D:** 0.76" (19.50mm)



**MATERIAL**  
Anodized Aluminum



**DESCRIPTION**  
Small surfaced mounted or hanging channel with wrap around lens.



**LENGTH**  
2 meter



**LENS TYPES**  
 Clear CHW-SH-2027-CC  
 Frosted CHW-SH-2027-CF  
 Milky CHW-SH-2027-CM



**ACCESSORIES**  
 Endcap CHW-SH-2027-EC  
 End Cap w/hole CHW-SH-2027-ECH  
 Hanging Hardware CHW-SH-MW  
 Bracket Straight CHW-SH-BS  
 Bracket 90° Flat CHW-SH-B90F  
 Bracket 90° Raised CHW-SH-B90R


*\*Must specify for hanging or surface mount application.*

## MOUNTING OPTIONS - COMPATIBLE CHANNELS

- Not Blended  
 Blended w/Milky Lens  
 **1** Configuration 1  
 **1a** Configuration 1 with Auxiliary Housing Accessory  
 **2** Configuration 2  
 **3** Configuration 3

## SPECIALTY CHANNELS

### CHW-S/H-3561




**A:** 1.38" (35.00mm)    **C:** 2.43" (61.70mm)  
**B:** 1.24" (31.40mm)    **D:** 1.57" (39.90mm)

	<b>MATERIAL</b> Anodized Aluminum
<b>1</b>	<b>DESCRIPTION</b> Large surface mounted or hanging channel with wrap around lens.
<b>2</b>	<b>LENGTH</b> 2 meter
	<b>LENS TYPES</b> Milky CHW-SH-3561-CM
	<b>ACCESSORIES</b> Endcap CHW-SH-3561-EC End Cap w/hole CHW-SH-3561-ECH Hanging Hardware CHW-SH-MW Bracket Straight CHW-SH-BS Bracket 90° Flat CHW-SH-B90F Bracket 90° Raised CHW-SH-B90R

\*Must specify for hanging or surface mount application.

### CHW-S/H-3030




**A:** 1.18" (30.00mm)  
**B:** 1.01" (25.60mm)  
**C:** 1.18" (30.00mm)

	<b>MATERIAL</b> Anodized Aluminum
<b>1</b>	<b>DESCRIPTION</b> Wide and deep surface mounted or hanging channel with flat lens for even blending.
<b>2</b>	<b>LENGTH</b> 2 meter
	<b>LENS TYPES</b> Milky CHW-SH-3030-CM
	<b>ACCESSORIES</b> Endcap CHW-SH-3030-EC Endcap w/hole CHW-SH-3030-ECH Hanging Hardware CHW-SH-MW Bracket Straight CHW-SH-BS Bracket 90° Flat CHW-SH-B90F Bracket 90° Raised CHW-SH-B90R End Cap for FLEX AC CHW-SH-3030-ECAC Mounting Clip for FLEX AC CHW-SH-3030-MCAC VHB Tape VHBTAPE.AC

\*Must specify for hanging or surface mount application.

### CHW-S/H-7532




**A:** 2.95" (75.00mm)  
**B:** 2.52" (64.00mm)  
**C:** 1.26" (32.00mm)

	<b>MATERIAL</b> Anodized Aluminum
<b>1</b>	<b>DESCRIPTION</b> Wide surface mounted or hanging channel with flat lens.
<b>2</b>	<b>LENGTH</b> 2 meter
	<b>LENS TYPES</b> Frosted CHW-SH-7532-CF
	<b>ACCESSORIES</b> Endcap CHW-SH-7532-EC Endcap w/hole CHW-SH-7532-ECH Hanging Hardware CHW-SH-MW Bracket Straight CHW-SH-BS Bracket 90° Flat CHW-SH-B90F Bracket 90° Raised CHW-SH-B90R

\*Must specify for hanging or surface mount application.


### CHC-S-1921



**A:** 0.76" (19.43mm)  
**B:** 0.55" (14.09mm)  
**C:** 0.84" (21.43mm)


	<b>MATERIAL</b> Anodized Aluminum
<b>2</b>	<b>DESCRIPTION</b> Surface mount channel with flat lens. Mounts to ferrous and non-ferrous surfaces using magnets with no visible fasteners once mounted.
<b>3</b>	<b>LENGTH</b> 2 meter
	<b>LENS TYPES</b> Milky CHC-S-1921-CM
	<b>ACCESSORIES</b> Anodized Aluminum Endcap CHC-S-1921-EC Anodized Aluminum Endcap w/hole CHC-S-1921-ECH Channel Mounted Magnet CHC-S-1921-MA Wall Mounted Magnet CHC-S-1921-M 1" Mounting Plate CHC-S-1921-B1

### CHSP-S-1618



**A:** 0.63" (16.00mm)    **C:** 0.49" (11.90mm)  
**B:** 0.40" (10.16mm)




	<b>MATERIAL</b> Anodized Aluminum
<b>2</b>	<b>DESCRIPTION</b> Includes an aluminum insert that allows selection between (4) different beamspreads based on the position of the insert.
<b>3</b>	<b>LENGTH</b> 2 meter
	<b>LENS TYPES</b> Focusing Lens CHSP-S-1618-CFL
	<b>ACCESSORIES</b> Endcap CHSP-S-1618-EC Endcap w/hole CHSP-S-1618-ECH Mounting Clip CHSP-S-1618-MC



## ACCESSORIES




### LC-I2P-M

Indoor Lead Connector  
(Male)






### LC-I2P-F

Indoor Lead Connector  
(Female)






### FLEX.ZIP

Strain Relief Clip



### FLEXMNT.SIL.INT




Indoor Mounting Clip



### PFC-HO-1208-SS-KIT

**1a** Configuration 1 with  
Auxiliary Housing Accessory




Flex Connect Auxiliary Housing  
Accessory



### PFC-HO-1715-SS-KIT

**1a** Configuration 1 with  
Auxiliary Housing Accessory

Flex Connect Auxiliary Housing  
Accessory






## ACCESSORIES

### FLEX STP.PFC-02.10

Field installed FLEX Connect® power feed  
- 2 Conductor for 10mm Strip





Fits in all channel **except**:

- CHS-R-1208
- CHS-R-1715
- CHS-S-1208
- CHS-S-1715
- CHS-C-1919
- CHS-C-1616
- CHC-S-1921
- CHSP-R-2970
- CHSP-S-1618
- CHSP-STEP-8142

### FLEXSTP.BSC.02.10

Field installed FLEX Connect® butt splice -  
2 Conductor for 10mm Strip




Fits in all channel **except**:

- CHS-R-1208
- CHS-R-1715
- CHS-S-1208
- CHS-S-1715
- CHS-C-1919
- CHS-C-1616
- CHC-S-1921
- CHSP-R-2970
- CHSP-S-1618
- CHSP-STEP-8142


### LO-18G-2C-W-72

6' wire lead for FLEX Connect®  
(not in-wall rated)




### LP-18G-2C-W-72

6' Plenum rated wire lead for  
FLEX Connect™




### LO-18G-2C-W-SP

1000' spool of wire for  
FLEX Connect® (not in-wall rated)



### LP-18G-2C-W-SP


500' box of Plenum rated wire for  
FLEX Connect®



## CONFIGURATION TYPES


### 1 FLEX cut to length with FLEX Connect® Power Feeds for Field Termination, Channel uncut for field cutting

- Specify **FLEXConfig-1**
- Specify FLEX type and channel type
- FLEX factory cut to length, but not terminated
- One FLEX Connect® power feed connector and 6' lead provided per FLEX run
  - Uncut rolls of lead wire can also be provided (see page 8 for part #)
- Channel shipped uncut for field cutting.
- Specify number of butt splices (not shown - see page 8)
- IP68 not available in **FLEXConfig-1**
- JA8 2016 not available in **FLEXConfig-1**
- FLEXConfig-1** is quick ship if run lengths are provided at time of order. Take offs, if needed, will add lead time.
- The below channels are **NOT** compatible with FLEX Connect®:
  - Slim:**
    - CHS-R-1208
    - CHS-R-1715
    - CHS-S-1208
    - CHS-S-1715
    - CHS-C-1616
    - CHC-S-1921
  - Specialty:**
    - CHSP-R-2970
    - CHSP-S-1618
    - CHSP-STEP-8142




### 2 Cut To Length With Soldered Leads, Assemble On-Site <sup>1, 2, 3</sup>

- Specify **FLEXConfig-2**
- Specify FLEX type and channel type
- Specify run lengths
- IP68 only available in **FLEXConfig-2**
- If no config is specified, and run lengths are provided, **FLEXConfig-2** will be used



### 3 Pre-Assembled Factory Finished Fixtures <sup>1, 2</sup>


- Specify **FLEXConfig-3**
- Fully assembled fixture
- ETL stamped and listed as a fixture
- 6.50' max length
- Standard 6' power lead unless otherwise specified
- The below channels **CANNOT** be factory assembled:
  - Slim:**
    - CHS-R-1208
    - CHS-R-1715
  - Wide:**
    - CHW-R-2010
    - CHW-S-2027
    - CHW-S-7532
    - CHW-S-2623
    - CHW-S-3030
    - CHW-S-3561



#### NOTES:

- Due to the nature of the FLEX STP product, specific lengths may not fall exactly on a cutting point. In this case, Optic Arts® will always cut to the smaller dimension unless otherwise specified.
- Unless otherwise specified, channel is cut 15mm longer than FLEX STP.
- Some on-site assembly required. See installation guides for details.

## COMPATIBLE DRIVERS



## MLV (MLV)

PART	DESCRIPTION
ML10S24VDC	10W 120VAC DIMMABLE DRIVER
ML20S24VDC	20W 120VAC DIMMABLE DRIVER
ML35S24VDC	35W 120VAC DIMMABLE DRIVER
ML35S24VDC-277	35W 277VAC DIMMABLE DRIVER
ML40S24VDC	40W 120VAC DIMMABLE DRIVER
ML50S24VDC	50W 120VAC DIMMABLE DRIVER
ML50S24VDC-277	50W 277VAC DIMMABLE DRIVER
ML60S24VDC	60W 120VAC DIMMABLE DRIVER
ML75S24VDC	75W 120VAC DIMMABLE DRIVER
ML75S24VDC-277	75W 277VAC DIMMABLE DRIVER
ML96S24VDC	96W 120VAC DIMMABLE DRIVER
ML96S24VDC-277	96W 277VAC DIMMABLE DRIVER
EM2-200S24DC	200W 120VAC DIMMABLE DRIVER, 2 96W CIRCUITS
EM3-300S24DC	300W 120VAC DIMMABLE DRIVER, 3 96W CIRCUITS
EM2-200S24DC-277	200W 120VAC DIMMABLE DRIVER, 2 96W CIRCUITS
EM3-300S24DC-277	288W 120VAC DIMMABLE DRIVER, 3 96W CIRCUITS

### DIMENSIONS


10W-50W	H 2.11"; W 7.38"; D 1.60"
60W-96W	H 3.93"; W 8.13"; D 1.59"
200-300W	H 5.69"; W 10.29"; D 3.13"

### DIMMING PERFORMANCE

MLV DRIVER Dims to 20% on most MLV dimmers

NOTE: Must be loaded between 75%-100% of rated load to maintain FLEX DC® warranty

### 120 VAC WIRING



## PURE DC™ MLV (PDC)

PART	DESCRIPTION
PDC.40.24	40W 120/277VAC PURE DC™ MLV DIMMABLE DRIVER
PDC.96.24	96W 120/277VAC PURE DC™ MLV DIMMABLE DRIVER


### DIMENSIONS

40W	L 14.25"; W 3.00"; H 2.88"
96W	L 14.75"; W 4.31"; H 4.81"


### DIMMING PERFORMANCE

PURE DC™ DRIVER Dims to 0.1% on most MLV dimmers

### 277 VAC WIRING




## COMPATIBLE DRIVERS



## ELECTRONIC DRIVER - NON-DIM (ND)

PART	DESCRIPTION
GG100E-24-UNV	96W 120-277VAC ELECTRONIC DRIVER
<b>DIMENSIONS</b>	
ELECTRONIC DRIVER	H 3.00"; W 11.46"; D 1.30"
<b>DIMMING PERFORMANCE</b>	
ELECTRONIC DRIVER	Non-Dim




## ELECTRONIC DRIVER W/0-10V MODULE (010)


PART	DESCRIPTION
GG100E-24-UNV-010V	96W 120-277VAC ELECTRONIC DRIVER WITH 0-10V DIMMING MODULE (SINK)
<b>DIMENSIONS</b>	
ELECTRONIC DRIVER - 0-10V	H 3.00"; W 11.46"; D 1.30"
<b>DIMMING PERFORMANCE</b>	
ELECTRONIC DRIVER - 0-10V	Dims below 1% on most 0-10V dimmers

### FIELD INSTALLED IN LOW VOLTAGE WIRING COMPARTMENT

- Install DIM-010V Module in low voltage wiring compartment.
- Max number of 25 modules on one dimmer. Consult dimmer datasheet for maximum device limitation of a specific controller.



## COMPATIBLE DRIVERS



For more options to wire DMX module, reference [DMX System](#) cut sheet.

## ELECTRONIC DRIVER W/DMX MODULE (DMX)

PART	DESCRIPTION
GG100E-24-UNV-DMX	96W 120-277VAC ELECTRONIC DRIVER WITH eldoLED DMX DIMMING MODULE

### DIMENSIONS

96W	H 3.00"; W 11.46"; D 1.30"
DMX MODULE	H 1.97"; W 6.02"; D 0.91"


\*Must be installed in UL box (by others)

### DIMMING PERFORMANCE


ELECTRONIC DRIVER - DMX MODULE	Dims to 0.1% on most DMX systems
--------------------------------	----------------------------------

COMPATIBLE DRIVERS

### DIMMER WITH NEUTRAL



### DIMMER WITHOUT NEUTRAL





**LUTRON HI-LUME® 1% 2-WIRE:**  
2-WIRE CONTROL FORWARD PHASE



PART	DESCRIPTION
LTEA4U1UKL-CV240	5-40W, 120VAC, 2-WIRE FORWARD PHASE DRIVER
DIMENSIONS	
HI-LUME® 1% 2-WIRE	H 4.00"; W 4.89"; D 2.62"
DIMMING PERFORMANCE	
LUTRON HI-LUME® 1% 2-WIRE	Dims to 1% with compatible Lutron controls

COMPATIBLE DRIVERS



**LUTRON HI-LUME® 1%:**  
3-WIRE/ECOSYSTEM




PART	DESCRIPTION
L3DA4U1UKL-CV240	5-40W, 120-277VAC, 3-WIRE/ECOSYSTEM DRIVER

DIMENSIONS	
HI-LUME® 1%	H 4.00"; W 4.89"; D 2.62"


DIMMING PERFORMANCE	
LUTRON HI-LUME® 1% 3-WIRE/ECOSYSTEM	Dims to 1% with compatible Lutron controls

COMPATIBLE DRIVERS

### 3-WIRE



### ECOSYSTEM



### LUTRON HI-LUME® PREMIER: 3-WIRE/ECOSYSTEM



PART	DESCRIPTION
L3D0-96W24V-U	2-96W, 120-277VAC, 3-WIRE/ECOSYSTEM DRIVER

DIMENSIONS	
HI-LUME® PREMIER	H 5.5"; W 10.5"; D 2.0"

DIMMING PERFORMANCE	
LUTRON HI-LUME® PREMIER	Dims to 0.1% with compatible Lutron controls
<i>NOTE: Lutron soft-on, fade to black technology available with Ecosystem Digital Control only.</i>	









TM-30 - 1800K

**Rf 85.7**  
Fidelity index Rf

**Rg 86.4**  
Gammut index Rg

Hue Bin	R <sub>f</sub>	Graphic shifts (%)	
		Chroma	Hue
1	93	-2%	0%
2	87	-3%	-5%
3	77	-6%	-10%
4	80	-14%	-8%
5	86	-17%	1%
6	73	-11%	13%
7	77	-7%	12%
8	80	0%	14%
9	93	1%	3%
10	95	1%	-2%
11	87	-2%	-7%
12	85	-3%	-8%
13	82	-7%	-11%
14	83	-13%	-10%
15	87	-8%	2%
16	88	-6%	3%



# FLEX STP 40







# Specification Sheet

TM-30 - 2350K

**Rf 94.5**  
Fidelity index Rf

**Rg 102.9**  
Gammut index Rg

Hue Bin	R <sub>f</sub>	Graphic shifts (%)	
		Chroma	Hue
1	96	-1%	1%
2	97	0%	1%
3	94	1%	2%
4	95	-1%	-1%
5	95	0%	1%
6	94	3%	1%
7	95	1%	0%
8	97	2%	-1%
9	96	1%	2%
10	96	1%	2%
11	92	4%	3%
12	93	4%	-1%
13	91	3%	-7%
14	90	3%	-6%
15	95	0%	-2%
16	90	1%	-7%



1130 Monterey Pass Rd, Monterey Park, CA 91754  
213.250.6069 | customerservice@opticsarts.com | www.opticsarts.com

Optic Arts reserves the right to modify this specification without prior notice.  
Last Modified: February 19, 2019 3:59 PM









TM-30 - 2750K

**Rf 93.3**  
Fidelity index Rf

**Rg 101.2**  
Gammut index Rg

Hue Bin	R <sub>f</sub>	Graphic shifts (%)	
		Chroma	Hue
1	95	-1%	1%
2	97	0%	1%
3	95	0%	2%
4	93	-3%	-1%
5	95	-1%	1%
6	97	1%	0%
7	92	-2%	2%
8	98	0%	1%
9	93	0%	4%
10	90	1%	6%
11	89	4%	6%
12	91	5%	0%
13	94	2%	-3%
14	91	4%	-5%
15	94	-1%	-1%
16	88	1%	-8%



# FLEX STP 40







# Specification Sheet

TM-30 - 2930K

**Rf 91.3**  
Fidelity index Rf

**Rg 99.5**  
Gammut index Rg

Hue Bin	R <sub>f</sub>	Graphic shifts (%)	
		Chroma	Hue
1	93	-2%	2%
2	95	0%	1%
3	95	0%	1%
4	91	-4%	-3%
5	94	-3%	0%
6	96	-1%	0%
7	89	-4%	4%
8	95	-1%	2%
9	89	0%	6%
10	86	2%	8%
11	87	5%	7%
12	90	5%	0%
13	93	1%	-5%
14	90	3%	-6%
15	91	-3%	0%
16	87	1%	-9%



TM-30 - 3550K

**Rf 91.9**  
Fidelity index Rf

**Rg 101.0**  
Gammut index Rg

Hue Bin	R <sub>f</sub>	Graphic shifts (%)	
		Chroma	Hue
1	95	0%	1%
2	97	0%	0%
3	95	0%	1%
4	93	-2%	0%
5	91	-4%	0%
6	96	0%	1%
7	94	-3%	2%
8	95	-1%	2%
9	91	-1%	5%
10	86	0%	9%
11	85	4%	9%
12	89	4%	3%
13	96	2%	-1%
14	92	6%	-2%
15	91	2%	-2%
16	89	2%	-5%

